Metamark 7 Series

High Performance Calendered Sign Vinyl



Product Description

Metamark 7 Series is a high performance calendered vinyl developed for computer-cut graphics for vehicles, window decals, and long term applications onto flat or slightly curved surfaces. The soft handle 70 micron face film offers ease of weeding, while the high grade solvent based adhesive allows wet application and clean removal. Exterior durability is 8 years for black and white, 7 years for colours and 5 years for metallic colours. M7-100 White Gloss and M7-101M White Matt have a blue contrast liner.

Features & Benefits

- Premium Grade Plotter Vinyl
- Apex® permanent Solvent based adhesive for clean removability.
- Metasure warranty up to 8 years.

- Available with Metascape® air release.
- · Contemporary colour range of 90 colours.
- Engineered to give long term dimensional stability.

Face Film	Polymeric calendered PVC	Finishes Available	87 Gloss and 3 Matt
Gauge	70 micron nominal	Durability	
Adhesive		Shelf Life	2 years. (10-20°C and 50% R.H).
Type Adhesion to glass 20 mins Adhesion to glass 24 hour Perceived Tack	Permanent solvent-based acrylic 15N/25mm nominal 20N/25mm nominal Medium	External weathering	8 years for black and white, 7 years for colours and 5 years for metallic; in vertical exposure under northern European conditions.
Shear Strength Application temperature Service temperature	Medium to High +10°C to +50°C -30°C to +110°C	Fire Rating	Class B - BS EN 13501-1:2007 Class 0 - BS 476 pt7 (glass + Painted 3mm Aliminium)
Release Liner		Chemical Resistance	Resistant to mineral oils, fats and
Print Weight Type	Metamark 7 Series in Purple print 135 gsm nominal Solventless, clay coated, layflat Kraft	I	fuels, aliphatic solvents, mild acids, salt and alkali for e.g. diesel oil, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.
		Regulations	REACH & RoHS compliant

Application

- ideal for use on external applications including vehicle graphics and exterior sign applications.
- Suitable for plotter use, also for contour and vinyl lettering.
- Suitable for wet or dry application.
- Apply unstressed, in particular to curves and recesses. It is not suitable for application over rivets or complex recesses.
- Some Yellows and Tangerine are not suitable for use on darker Substrates due to low opacity.
- Not recommended for use on low energy surfaces such as polypropylene.
- The user should determine suitability of substrate.

MetaSure® Warranty

Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.



Metamark Crystal, Dusted and Silver Etch

Premium Etch Glass Effect Films



Product Description

Metamark Crystal Etch, Dusted Etch and Silver Etch films are polymeric calendered etch effect vinyls, specially formulated for producing fine window decals and manifestation. The 70 micron film and high quality release liner and adhesive provide fast cutting and easy weeding on all computerised sign making equipment. The vinyl is resistant to most mineral oils, fats and fuels, aliphatic solvents, mild acids, diesel, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.

Typical Applications

- For computer-cut etched glass effect graphics, and window manifestation.
- Crystal Etch offers a subtle glitter effect, Silver Etch is suitable for decals where a higher level of opacity is required, while Dusted Etch provides a higher level of transparency for more subtle window markings.

Application Guidelines

- Suitable for wet application.
- Not suitable for use on Polycarbonate. Application between two sheets of glass is not recommended.
- Refer to www.metamark.co.uk/technical for further advice on application to glass.

Face Film	Re	
Face Film: Gauge: Tensile Strength	Polymeric matt calendered PVC 70 micron nominal 47N/25mm MD / 43N/25mm TD	Тур
Elongation at break Shrinkage	180% MD nominal -0.5% MD, -0.2% TD	Gai We
Adhesive		Fin
Type Weight Adhesion to glass 20 mins Adhesion to glass 24 hour	Permanent solvent-based adhesive 22gsm nominal 15N/25mm nominal 20N/25mm nominal	Fin
Perceived tack Shear strength	Medium Medium to High	Du
Application temperature Service temperature	+5°C to +60°C -30°C to +110°C	She Ext
Light Transmission		Fire
Dusted Etch Silver Etch Crystal Etch	88% 56% 57%	Che

Release Liner		
Туре	An advanced specially treated layflat kraft paper with high internal strength and PE coating	
Gauge Weight	145mym nominal 140 gsm nominal	
Finishes		
Finishes Available	M7-CR Crystal Etch M7-DE Dusted M7-SE Silver Etch	
Durability		
Shelf Life External weathering Fire Rating Chemical Resistance	1 year 7 years in vertical exposure under Northern European conditions Class B. Classification compliant with BS EN 13501-1:2007 Resistant to mineral oils, fats and fuels, aliphatic solvents, mild acids, salt and alkali for e.g. diesel oil, gasoline, paraffin, hydraulic oil, antifreeze, soap suds etc.	

Warranty: Metamark (UK) Limited warrants to its customers that completed decorative markings which utilise Metamark SignVinyl will remain in good condition without excessive fading or colour degradation for the specified life time of each material when correctly stored and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark SignVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will also, at its own discretion, contribute an allowance towards the costs involved in replacing the graphics. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark 7 Series High Performance Calendered Sign Vinyl





M7-105 Clear
M7-101M AH White Matt
M7-100 AH White Gloss
M7-109 A Chiltern White
M7-122 A Pale Grey
M7-121 A Light Grey
M7-123 Medium Grey
M7-120 Pewter
M7-127 Ash Grey
M7-124 A Dark Grey
M7-125 AH Nimbus Grey
M7-128 Shadow
M7-126
Storm Grey M7-111M AH
M7-110 AH
Black Gloss
M7-194 A Steel
M7-195 A Aluminium
M7-190 ^A Silver
M7-193M ^A Gunmetal
M7-192 A Charcoal
M7-196 ^A Graphite
M7-191 ^A Gold

Product Description

Premium grade high performance calendered vinyl, developed for computercut graphics for vehicles, window decals, and long term applications onto flat or slightly curved surfaces.

The soft handle 70 micron face film offers ease of weeding, while the Apex high grade solvent based adhesive allows wet application and clean removal.

Specifications	
Face Film	70 Micron Polymeric calendered PVC
Adhesive	Permanent solvent-based acrylic Apex: Supplied as standard MetaScape: Available on certain colours High Tack: Available on certain colours
Application Temperature	+5°C to +60°C
Release Liner	Structured Layflat Kraft Liner
Shelf Life	2 years
External Weathering	8 years black and white, 7 years colours, 5 years for metallics. Vertical exposure under Northern European conditions. For other regions and climates please refer to our full Durability Guide found on our website.
Fire Rating	Class B. BS EN 13501-1:2007

MetaScape Adhesive System

MetaScape offers faster, trouble-free application of larger areas on flat or slightly curved surfaces. The MetaScape Adhesive System provides air with an exit route through channels within the adhesive. MetaScape is suitable for dry application methods, resulting in a durable graphic that is ready much sooner after installation.



High Tack Adhesive System

The High Tack Adhesive System has been developed to apply to 'difficult to stick to' surfaces, smooth low energy plastics such as PE and PP, and for smooth sealed interior wall decor applications. The High Tack adhesive provides enhanced adhesion and a high grade solvent-based adhesive which allows for wet application.



A Indicates colour available with the optional MetaScape adhesive system. Please specify at point of ordering.

[&]quot;Indicates colour available with the optional High Tack adhesive system. Please specify at point of ordering.